INFRALAN® RJ45 patch cable 10 Gigabit Ethernet Cat.6A 500 MHz,

INFRALAN® RJ45 patch cable 10 Gigabit Ethernet Cat.6A 500 MHz,

halogen-free, with 2 x RJ45 Hirose TM31 plugs, IEC 60603-7-51, mounted bend protection sleeve with snap-in nose protection, with Draka UC900 S/FTP PiMF. Suitable for PoE standards IEEE802.3AF and AT. Tertiary (horizontal) applications; IEEE802.3: 10Base-T; 100Base-T; 100Base-T; 10GBase-T, IEEE802.5: 16 MB; ISDN; TPDDI; ATM

Cable construction: S/FTP 4 x 2 x AWG27/7 PiMF, LSZH Ø=5.9 mm

Assignment: 1:1, TIA/EIA 568B

Flame retardancy according to: IEC 60332-1

halogen-free: IEC 60754-2

low smoke after: IEC 61034

Temperature range: -20°C to +60°C

Length: 1,0m

Colour: grey

Make: INFRALAN®

Item no.: IPK-6A-M-HFR-GR-0100

INFRALAN® RJ45 patch cable 10 Gigabit Ethernet Cat.6A 500 MHz,

INFRALAN® RJ45 patch cable 10 Gigabit Ethernet Cat.6A 500 MHz, with 2 x Hirose TM31 connectors as described above, however:

Length: X,Xm

, ,

Color: XX

Make: INFRALAN®

Part No.: IPK-6A-M-HFR-XX-XXXX

Structure Art. no:

IPK-6A-M-HFR-XX-XXXX

Available in colours:

Available in lengths:

0,50m / 1,00m / 1,50m / 2,00m / 3,00m / 5,00m / 7,50m / 10,00m / 15,00m / 20,00m