

## FTTH IP65 connection box 24 ports

FTTH IP65 connection box 24 ports,

unpopulated 24-ports connection box made of plastic suitable for SC-Simplex/ LC-Duplex/ E2000® couplings, which has an overlength fibre holder. In addition to a swivelling splice cassette, the connection box contains a holder for splitters and a cable sheath. The FTTH IP65 connection box offers space for up to four gas blockers, speedpipes can be inserted.

This box is used in optical telecommunication networks, LAN, CATV networks, FTTH networks as well as PON and G-PON.

Supplied with shrink splice protection and wall mounting material.

Field of application: Exterior

Mounting type: Wall mounting

Possibility of mast mounting: Yes

Material: plastic

Colour: Grey

Number of cable entries: 26 (24x 2-3mm; 2x PG19)

Maximum number of fibres: 48

Splice protection type: Shrink

Coupling type: SC Simplex/LC Duplex/E2000®

Max. Equipment (adapter): 24

Insertable Speedpipes, max. 4 Gasblocker

IP Protection class IP65

Protection against foreign bodies and contact: Protection against dust ingress

Water protection: Protection against water jets

Dimensions: hxbxt 232mm x 359mm x 130,5mm

Temperature range: -25°C - 70°C

Access protection: Special Screw

Make: EFB-Elektronik GmbH

Part No.: FTTH-BOX-OUT-5