

DATASHEET

DIN Rail Box Front Panel empty 1.7 mm, 12x SC Simplex / LC Duplex / E2000®



General data

Front plates for 53705.1V3

Without adapters

Technical properties

Material	Metal
Temperature Range (Operation)	-40 - 75 °C
Type of plug-in connector system	Fiber Optic
With buses/couplings	False

Available variants

ArtNr.	Bezeichnung	Colour	Number of connector holes	Suitable for adapter	Mounting holes	RAL number
53705.2V2B	DIN Rail Box Front Panel empty 2.8 mm, for 6x SC Duplex / LC Quad	light grey	6	SC Duplex/LC Quad	2.8 mm	7035

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.

DATASHEET

DIN Rail Box Front Panel empty 1.7 mm, 12x SC Simplex / LC Duplex / E2000®

53705.2V2B2	DIN Rail Box Front Panel empty 1.7 mm, for 6x SC Duplex / LC Quad	light grey	6	SC Duplex/LC Quad	1.7 mm	7035
53705.3V2B	DIN Rail Box Front Panel empty 2.8 mm, for 6x SC Simplex / LC Duplex / E2000®	light grey	6	SC Simplex/LC Duplex/E2000®	2.8 mm	7035
53705.3V2B2	DIN Rail Box Front Panel empty 1.7 mm, for 6x SC Simplex / LC Duplex / E2000®	light grey	6	SC Simplex/LC Duplex/E2000®	1.7 mm	7035
53705.4V2B	DIN Rail Box Front Panel empty 2.8 mm, for 12x SC Simplex / LC Duplex / E2000®	light grey	12	SC Simplex/LC Duplex/E2000®	2.8 mm	7035
53705.4V2B2	DIN Rail Box Front Panel empty 1.7 mm, 12x SC Simplex / LC Duplex / E2000®	light grey	12	SC Simplex/LC Duplex/E2000®	1.7 mm	7035
53705.5V2B	DIN Rail Box Front Panel empty, for 12x ST Simplex	light grey	12	ST-Simplex	7035	

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.

