

DATASHEET

RJ45 Cat.6 IP68 adapter, Jack/Jack Connection module



General data

IP68 cable connector for outdoor installation and direct burial. Integrated Cat.6 RJ45 jack to facilitate connection. Designed for transmissions up to 250MHz according to ISO/IEC 11801 ClassE and Data transmission rate up to 5 Gbit/s.

- Easy installation
- Waterproof cable connector of protection class IP68
- Max. Voltage of 125V and max. current of 1.5A
- Cable gland in PG16
- For cables with a diameter of 4,5 mm- 10 mm
- L x D 121.5mm x 28 mm

Technical properties

Assembly	Cable duct
Category	6
Construction type	straight
Model	jack/jack
Temperature Range (Operation)	0 - 70 °C
Type of connector	2x RJ45
UV resistant	True

Available variants

ArtNr.	Bezeichnung	screened
IP68DFKRJ45WP	RJ45 Cat.6 IP68 adapter, Jack/Jack Connection module	True

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.