

DATASHEET

Front Door for Wall Housings 18U, Stahl, RAL7035



General data

Steel door for wall housing 1-part resp. 2-part
 1-point latch locking T3/1333
 Suitable for compact turning handle for profile half-cylinder (Art.-No. 699989)
 Paint finish RAL7035, light grey / RAL9005, jet black
 Delivery incl. 2 x key, hinges, earthing cable

Technical properties

Cabinet Series	Wall Housings 1/2-part
Degree of protection	IP20
Door opening angle	> 180 °
For Cabinet Width	600 mm
Material	Steel
Model	Stop door
Number of height units (U)	12
Profile half-cylinder exchangeable	False
Scope of delivery	Tür, inkl. Scharnieren, Erdungskabel, 2 x Schlüssel
Structure/Use	Steel door, 1-part, with 1 latch lock
Surface finishing	Powder coating
Type of closure	1-point latch locking mechanism, (optionally with compact swivel lever)
Version as glazed door	False

Available variants

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Front Door for Wall Housings 18U, Stahl, RAL7035

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
102130GR.15S	Front Door for Wall Housings 15U, Stahl, RAL7035	600 mm	grey	666 mm	596.5 mm	7035	False	False
102130GR.18S	Front Door for Wall Housings 18U, Stahl, RAL7035	600 mm	grey	799 mm	596.5 mm	7035	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

