

DATASHEET

Ribbon Cable, pitch 1.27, 30.5m 10-pole, AWG 28/7



General data

AWG28/7

Grey with identifier core (red)

30.5 m rolls

Individual wires, tin-plated

Technical properties

AWG-size	28
Conductor category	Class 2 = stranded
Core insulation	PVC
Diameter conductor	0.127 mm
Flame retardant	According to EN 60332-1-2
Halogen free (acc. EN 50267-2-2)	False
Low smoke (acc. EN 61034-2)	False
Low temperature resistant (acc. EN 60811-1-4)	False
Nominal cross section conductor	0.09 mm ²
Nominal voltage U	300 V
Oil resistant (acc. EN 60811-2-1)	False
Operating temperature, fix	-30..+105 - °C
Operating temperature, flexible	-20..+105 - °C
Screen	False

Available variants

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Ribbon Cable, pitch 1.27, 30.5m 10-pole, AWG 28/7

ArtNr.	Bezeichnung	Core colour	Number of conductor	Outer diameter approx.
22310B.30R	Ribbon Cable, pitch 1.27, 30.5m 10-pole, AWG 28/7	grey	10	0.93 mm
22314B.30R	Ribbon Cable, pitch 1.27, 30.5m 14-pole, AWG 28/7	grey	14	0.93 mm
22316B.30R	Ribbon Cable, pitch 1.27, 30.5m 16-pole, AWG 28/7	grey	16	0.93 mm
22320B.30R	Ribbon Cable, pitch 1.27, 30.5m 20-pole, AWG 28/7	grey	20	0.93 mm
22326B.30R	Ribbon Cable, pitch 1.27, 30.5m 26-pole, AWG 28/7	grey	26	0.93 mm
22334B.30R	Ribbon Cable, pitch 1.27, 30.5m 34-pole, AWG 28/7	grey	34	0.93 mm
22340B.30R	Ribbon Cable, pitch 1.27, 30.5m 40-pole, AWG 28/7	grey	40	0.93 mm
22350B.30R	Ribbon Cable, pitch 1.27, 30.5m 50-pole, AWG 28/7	grey	50	0.93 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

