

DATASHEET

Dsub Jack, IDC contacts flat version,E-DFF 09 LPIII/Z



General data

The D-Sub socket 9 pin from EFB-Elektronik in a flat design is designed for a reliable connection on the PCB or for flat cables. With a 180° connection angle and female contact design, it is suitable for compact connectors in technical applications.

- 9-pin D-sub socket in flat design
- 180° design with insulation terminal connection for flat cables
- Female contact design for suitable connectors

Due to the temperature range of -25 to 85 °C, the bushing is designed for typical technical environments. The EDFF 09 LPIII/Z version supports a stable signal connection on flat cables with a conductor cross-section of 28AWG to 26AWG.

Technical details

- Type: EDFF 09 LPIII/Z
- Connection type: other
- Shooting angle: 180°
- Finish: Socket
- Contact version: female
- For cable type: flat
- Conductor Cross Section: 28AWG ~ 26AWG
- Number of poles: 9
- Temperature range: -25 – 85 °C
- Brand: EFB-Elektronik
- Packaging: 90 pieces per blister

Technical properties

Conductor cross-section	28AWG ~ 26AWG
Connection angle (180°/90°)	180

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.



DATASHEET

Dsub Jack, IDC contacts flat version,E-DFF 09 LPIII/Z

Connection type	Other
Contact manufacturing method (turned/stamped)	stamped
Contact type	female
For cable type (round/flat)	flat
Model	jack
Temperature range	-25 - 85

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
29010.1	Dsub Jack, IDC contacts flat version,E-DFF 09 LPIII/Z	9	EDFF 09 LPIII/Z	90 pieces per tray	2
29011.1	Dsub Jack, IDC contacts flat version,E-DFF 15 LPIII/Z	15	EDFF 15 LPIII/Z	70 pieces per tray	2
29012.1	Dsub Jack, IDC contacts flat version,E-DFF 25 LPIII/Z	25	EDFF 25 LPIII/Z	40 pieces per tray	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.

