DATASHEET

Dsub Jack, IDC contacts flat version,E-DFF 25 LPIII/Z



General data

The 25-pin D-Sub socket from EFB-Elektronik in a flat design is designed for compact connectors with a female contact design. With a 180° connection angle and insulation displacement, it is suitable for standard-compliant integration on the printed circuit board and for applications with flat cables.

- 25-pin D-Sub socket for compact connections
- 180° version with female contact design
- For flat cables with conductor cross-section 28AWG to 26AWG

With a temperature range of -25 to 85 °C, the EDFF 25 LPIII/Z version is designed for demanding environments. The combination of flat design, insulation clamp and precise plug-in geometry supports a resilient signal connection in industrial and technical applications.

Technical details
- Type: EDFF 25 LPIII/Z
- Connection type: other
- Shooting angle: 180°
- Finish: Socket
- Contact version: female
- Number of poles: 25
- For cable type: flat
- Conductor Cross Section: 28AWG ~ 26AWG
- Temperature range: -25 – 85 °C
- Brand: EFB-Elektronik
- Packaging: 40 pieces per blister

Technical properties

Conductor cross-section	28AWG ~ 26AWG

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Dsub Jack, IDC contacts flat version,E-DFF 25 LPIII/Z

Connection angle (180°/90°)	180
Connection type	Other
Contact manufacturing method (turned/stamped)	stamped
Contact type	female
For cable type (round/flat)	flat
Model	jack
Temperature range	-25 – 85

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
29010.1	Dsub Jack, IDC contacts flat version,E-DFF 09 LPIII/Z	9	EDFF 09 LPIII/Z	90 pieces per tray	2
29011.1	Dsub Jack, IDC contacts flat version,E-DFF 15 LPIII/Z	15	EDFF 15 LPIII/Z	70 pieces per tray	2
29012.1	Dsub Jack, IDC contacts flat version,E-DFF 25 LPIII/Z	25	EDFF 25 LPIII/Z	40 pieces per tray	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION