

DATASHEET

DSub Plug, IDC contacts flat version, E-DSF 09 LPIII/Z



General data

The D-Sub connector 9 pin from EFB-Elektronik is designed for use with a flat cable and as a version with insulation displacement. With a 180° connection angle and male contact design, it is suitable for compact, standard-compliant connectors in technical applications.

- 9-pin D-Sub connector in flat design
- 180° design for connection with flat cable
- Male contact design for a suitable plug connection

Due to the temperature range of -25 to 85 °C, the connector is intended for demanding environments. The EDSF 09 LPIII/Z version supports a stable signal connection when a precise and permanently resilient interface is required in industrial or technical applications.

Technical details

- Type: EDSF 09 LPIII/Z
- Connection type: other
- Shooting angle: 180°
- Type: Plug
- Contact version: male
- Number of poles: 9
- For cable type: flat
- Conductor Cross Section: 28AWG ~ 26AWG
- Temperature range: -25 – 85 °C
- Brand: EFB-Elektronik
- Packaging: 90 pieces per blister

Technical properties

Conductor cross-section	28AWG ~ 26AWG
-------------------------	---------------

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

DSub Plug, IDC contacts flat version,E-DFF 09 LPIII/Z

Connection angle (180°/90°)	180
Connection type	Other
Contact manufacturing method (turned/stamped)	stamped
Contact type	male
For cable type (round/flat)	flat
Model	plug
Temperature range	-25 - 85

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
29060.1	DSub Plug, IDC contacts flat version,E-DFF 09 LPIII/Z	9	EDSF 09 LPIII/Z	90 pieces per tray	2
29061.1	DSub Plug, IDC contacts flat version,E-DFF 15 LPIII/Z	15	EDSF 15 LPIII/Z	70 pieces per tray	2
29062.1	DSub Plug, IDC contacts flat version,E-DFF 25 LPIII/Z	25	EDSF 25 LPIII/Z	40 pieces per tray	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

