

DATASHEET

DSub Plug, IDC contacts flat version,E-DFF 15 LPIII/Z



General data

The 15-pin D-Sub connector from EFB-Elektronik is designed for a reliable insulation displacement connection in a flat design. With a 180° design and male contact design, it is suitable for compact connectors with flat cables.

- 15-pin D-Sub connector in flat design
- 180° design with insulation displacement connection for flat cables
- Male contact design for matching connectors

With a conductor cross-section of 28AWG to 26AWG, the EDSF 15 LPIII/Z version supports stable contacting in technical applications. The temperature range of -25 to 85 °C makes the connector suitable for environments where a resilient and space-saving interface is required.

Technical details

- Type: EDSF 15 LPIII/Z
- Connection Type: Insulation Clamp
- Shooting angle: 180°
- Type: Plug
- For cable type: flat
- Contact version: male
- Conductor Cross Section: 28AWG ~ 26AWG
- Number of poles: 15
- Temperature range: -25 – 85 °C
- Brand: EFB-Elektronik
- Packaging: 70 pieces per blister

Technical properties

Conductor cross-section	28AWG ~ 26AWG
Connection angle (180°/90°)	180

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

DSub Plug, IDC contacts flat version,E-DFF 15 LPIII/Z

Connection type	Other
Contact manufacturing method (turned/stamped)	stamped
Contact type	male
For cable type (round/flat)	flat
Model	plug
Temperature range	-25 - 85

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
29060.1	DSub Plug, IDC contacts flat version,E-DFF 09 LPIII/Z	9	EDSF 09 LPIII/Z	90 pieces per tray	2
29061.1	DSub Plug, IDC contacts flat version,E-DFF 15 LPIII/Z	15	EDSF 15 LPIII/Z	70 pieces per tray	2
29062.1	DSub Plug, IDC contacts flat version,E-DFF 25 LPIII/Z	25	EDSF 25 LPIII/Z	40 pieces per tray	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

