DATASHEET

DSub Plug, IDC contacts flat, version, E-DFF 15 LPIII/Z
















General data
Gütestufe III. ≥ 50 Steckzyklen. Kontaktmaterial: Vernickeltes Messing vergoldet

Technical properties	
Conductor cross-section	28AWG ~ 26AWG
Connection angle (180°/90°)	180
Connection type	Other
Contact manufacturing method (turned/stamped)	stamped
Contact type	male
For cable type (round/flat)	flat
Model	plug

This datasheet was created automatically on 22-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

DSub Plug, IDC contacts flat, version, E-DFF 15 LPIII/Z

Temperature range	-25 – 85

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
29061.1V2	DSub Plug, IDC contacts flat, version, E-DFF 15 LPIII/Z	15	EDSF 15 LPIII/Z	70 Stück pro Blister	2
29062.1V2	DSub Plug, IDC contacts flat, version, E-DFF 25 LPIII/Z	25	EDSF 25 LPIII/Z	40 Stück pro Blister	2
29063.1V2	DSub Plug, IDC contacts flat, version, E-DFF 37 LPIII/Z	37	EDSF 37 LPIII/Z	30 Stück pro Blister	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION