

DATASHEET

DSub Plug, IDC contacts flat version,E-DFF 25 LPIII/Z



General data

The 25-pin D-Sub connector with insulation terminal from EFB-Elektronik is designed for flat cables and a reliable connector in compact applications. With a 180° connection angle and male contact design, it is suitable for standard-oriented connection solutions in various technical environments.

- 25-pin D-sub design for compact connectors
- 180° design with male contact design
- Suitable for flat cables with conductor cross-section 28AWG to 26AWG

Due to the temperature range of -25 to 85 °C, the connector is intended for more demanding operating conditions. The EDSF 25 LPIII/Z version supports a resilient connection in industrial and technical applications where a permanently stable interface is required.

Technical details

- Type: EDSF 25 LPIII/Z
- Connection type: other
- Shooting angle: 180°
- Type: Plug
- For cable type: flat
- Contact version: male
- Conductor Cross Section: 28AWG ~ 26AWG
- Number of poles: 25
- Temperature range: -25 – 85 °C
- Brand: EFB-Elektronik
- Packaging: 40 pieces per blister

Technical properties

Conductor cross-section	28AWG ~ 26AWG
-------------------------	---------------

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

DSub Plug, IDC contacts flat version,E-DFF 25 LPIII/Z

Connection angle (180°/90°)	180
Connection type	Other
Contact manufacturing method (turned/stamped)	stamped
Contact type	male
For cable type (round/flat)	flat
Model	plug
Temperature range	-25 - 85

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
29060.1	DSub Plug, IDC contacts flat version,E-DFF 09 LPIII/Z	9	EDSF 09 LPIII/Z	90 pieces per tray	2
29061.1	DSub Plug, IDC contacts flat version,E-DFF 15 LPIII/Z	15	EDSF 15 LPIII/Z	70 pieces per tray	2
29062.1	DSub Plug, IDC contacts flat version,E-DFF 25 LPIII/Z	25	EDSF 25 LPIII/Z	40 pieces per tray	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

