
DATASHEET


DSub Plug, IDC contacts, flat, 09-pole, E-DSF 09 LPIII/Z UNC















General data

- Quality level III
- UNC thread
- 50 mating cycles

Technical properties	
Conductor cross-section	28AWG ~ 26AWG
Connection angle (180°/90°)	180
Connection type	Other
Contact manufacturing method (turned/stamped)	stamped
Contact type	male

This datasheet was created automatically on 22-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

DSub Plug, IDC contacts, flat, 09-pole, E-DSF 09 LPIII/Z UNC

For cable type (round/flat)	flat
Model	plug
Temperature range	-25 – 85

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
29065.1V2	DSub Plug, IDC contacts, flat, 09-pole, E-DSF 09 LPIII/Z UNC	9	EDSF 09 LPIII/Z UNC	90 pieces per tray	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION