

DATASHEET

Full Metal Cover DTZK 37-K



General data

The D-Sub full metal hood E-DTZK 37-K silver from EFB-Elektronik is designed as a hood made of die-cast zinc for 37-pin connectors. With a 180° cable outlet and straight cable entry, it is suitable for compact and standard-compliant cable connections in technical applications.

- Full metal hood in silver finish
- Suitable for 37-pin D-Sub connectors
- Cable outlet 180° with straight cable entry

The die-cast zinc material supports a robust protection solution for technical applications where a stable cover for D-Sub interfaces is required. The temperature range of -40 to 120 °C extends the scope of use for demanding environments, while the maximum cable diameter of 13 mm facilitates the integration of common cables.

Technical details

- Type: E-DTZK 37-K
- Material: Zinc die casting
- Colour: silver
- Suitable for Number of Poles: 37
- Cable entry: straight
- Cable outlet: 180°
- Temperature range: -40 – 120 °C
- Max. cable diameter: 13 mm
- Brand: EFB-Elektronik

Technical properties

Locking mechanism	Screw
Material	zinc die-cast
Separable	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Full Metal Cover DTZK 37-K

Temperature range	-40 - 120 °C
Two piece	True

Available variants

ArtNr.	Bezeichnung	Cable Entry	Cable diameter	Colour	Suitable for number of poles	Type	LxWxH
29446.1V2	Full Metal Cover DTZK 9-K	Straight	13 mm	silver	9	E-DTZK 9-K	38,3 x 31,2 x 14,6
29447.1	Full Metal Cover DTZK 15-K	Straight	13 mm	silver	15	E-DTZK 15-K	40,5 x 39,3 x 14,6
29448.1	Full Metal Cover DTZK 25-K	Straight	13 mm	silver	25	E-DTZK 25-K	47,8 x 53,4 x 14,6
29449.1	Full Metal Cover DTZK 37-K	Straight	13 mm	silver	37	E-DTZK 37-K	52,2 x 69,9 x 14,6

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

