

DATASHEET

DSub Crimp Housing for plugs, E-DFCR/25



General data

- Tin-plated housing
- Quality level III $\geq$ 50 mating cycles

Technical properties

Connection angle (180°/90°)	180
Connection type	crimp
Contact manufacturing method (turned/stamped)	stamped
Contact type	female
For cable type (round/flat)	round
Model	jack
Temperature range	-55 - 105

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

DSub Crimp Housing for plugs, E-DFCR/25

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
105878	DSub Crimp Housing for plugs, E-DFCR/15	15	E-DFCR/15	50 pieces per tray	2
34601.1	DSub Crimp Housing for plugs, E-DFCR/09	9	E-DFCR/09	50 pieces per tray	2
34601.1V2	DSub Crimp Housing for plugs, E-DFCR/09	9	E-DFCR/09	50 pieces per tray	2
34602.1	DSub Crimp Housing for plugs, E-DFCR/15	15	E-DFCR/15	50 pieces per tray	2
34602.1V2	DSub Crimp Housing for plugs, E-DFCR/15	15	E-DFCR/15	50 pieces per tray	2
34603.1V2	DSub Crimp Housing for plugs, E-DFCR/25	25	E-DFCR/25	50 pieces per tray	2
34604.1V2	DSub Crimp Housing for plugs, E-DFCR/37	37	E-DFCR/37	40 pieces per tray	2
34605.1	DSub Crimp Housing for plugs, E-DFCR/50	50	E-DFCR/50	50 pieces per tray	3

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

