

DATASHEET

DSub Jack 9.4mm Euro Standard, EDF 15, A/KG-T1



General data

Gütestufe III. UNC 4-40 Bolzen. PushFit Einrast Befestigungselement.

Technical properties

Connection angle (180°/90°)	90
Connection type	Solder
Contact manufacturing method (turned/stamped)	stamped
Contact type	female
Model	jack
Temperature range	-55 - 105

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

DSub Jack 9.4mm Euro Standard, EDF 15, A/KG-T1

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
34701.1V2	DSub Jack 9.4mm Euro Standard, EDF 09, A/KG-T1	9	EDF 09 A/KG-T1	90 Stück pro Blister	2
34702.1V2	DSub Jack 9.4mm Euro Standard, EDF 15, A/KG-T1	15	EDF 15 A/KG-T1	70 Stück pro Blister	2
34703.1V2	DSub Jack 9.4mm Euro Standard, EDF 25, A/KG-T1	25	EDF 25 A/KG-T1	50 Stück pro Blister	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

