DATASHEET

DSub Jack 9.4mm Euro Standard, EDF 25, A/KG-T1













General data
Gütestufe III. UNC 4-40 Bolzen. PushFit Einrast Befestigungselement.

Technical properties	
Connection angle (180°/90°)	90
Connection type	Solder
Contact manufacturing method (turned/stamped)	stamped
Contact type	female
Model	jack
Temperature range	-55 – 105

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

DSub Jack 9.4mm Euro Standard, EDF 25, A/KG-T1

Available variants

ArtNr.	Bezeichnung	Number of poles	Type	Packaging	Numbrt of rows
34701.1V2	DSub Jack 9.4mm Euro Standard, EDF 09, A/KG-T1	9	EDF 09 A/KG-T1	90 Stück pro Blister	2
34702.1V2	DSub Jack 9.4mm Euro Standard, EDF 15, A/KG-T1	15	EDF 15 A/KG-T1	70 Stück pro Blister	2
34703.1V2	DSub Jack 9.4mm Euro Standard, EDF 25, A/KG-T1	25	EDF 25 A/KG-T1	50 Stück pro Blister	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION