

DATASHEET

Kink protection sleeve RJ45 yellow, with Locking nose protection, PU 100



General data

Anti-Kink sleeve for 37541.3, 37514.1, 37519.1, 37539.1, 37640.1, 34600.1
Cable entry max. 6.6 mm

Technical properties

Application	RJ-plug
Flame retardant	UL-94V0
Suitable for	Round cable

Available variants

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



DATASHEET

Kink protection sleeve RJ45 yellow, with Locking nose protection, PU 100

ArtNr.	Bezeichnung	Colour	Min. inner diameter
37546.1-100	Kink protection sleeve RJ45 beige, with Locking nose protection, PU 100	beige	0.5 mm
37546.4-100	RJ45 anti-kink sleeve, black, with Locking nose protection, PU 100	Black	0.5 mm
37546.5-100	Kink protection sleeve RJ45 yellow, with Locking nose protection, PU 100	yellow	0.5 mm
37546.6-100	RJ45 kink protection sleeve, red, with Locking nose protection, PU 100	red	0.5 mm
37546.7-100	Kink protection sleeve RJ45 blue, with Locking nose protection, PU 100	blue	0.5 mm
37546.8-100	Bend protection sleeve RJ45 green, with Locking nose protection, PU 100	Green	0.5 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

