

DATASHEET

RJ45 connector STP, Cat.6, PU 100



General data

Up to 250 MHz (Cat.6)
 For stranded wires (AWG 24/7, AWG 26/7, AWG 27/7)
 Shielded version
 Core insulation about 0.9 - 1.0 mm
 Cable diameter max. 6.2 mm
 Suitable crimping tool DCW1003 + DCW1003.1

Anti-kink sleeve not included

Technical properties

Cable diameter	6.6 mm
Casing material	PC
Category	6
Connection type	crimp
Dust cover	No
For UAE suitable	False
Model	plug
Special tool necessary	True
Suitable for flat cable	False

This datasheet was created automatically on 29-09-2026 . Technical changes reserved.



DATASHEET

RJ45 connector STP, Cat.6, PU 100

Suitable for litz wire conductor	True
Suitable for round cable	True
Suitable for solid core	False
Type of connector	RJ45 8(8)
Type of locking	Crimp
screened	True

Available variants

ArtNr.	Bezeichnung	Colour
37640.1-100	RJ45 connector STP, Cat.6, PU 100	silver

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 29-09-2026 . Technical changes reserved.

