

DATASHEET

TM21DP-TM-88P(61) CAT6 Connector,TM21



Abb.
ähnlich



Abb.
ähnlich

General data

Channel Class E up to 250 MHz (Cat.6) for stranded wires (AWG 24/7, AWG 26/7, AWG 27/7)

Core insulation about 0.9 - 1.0 mm

Cable diameter max. 6.6 mm

Suitable crimping tool DCW1002 + DCW1002.1 or 39934.1

Technical properties

AWG-range	24 - 26
AWG-range for litz wire conductor	24 - 27
Cable diameter	6.6 mm
Casing material	PC
Category	6
Connection type	crimp
Dust cover	false
For UAE suitable	False
Model	plug
Special tool necessary	True
Suitable for flat cable	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

TM21DP-TM-88P(61) CAT6 Connector,TM21

Suitable for litz wire conductor	True
Suitable for round cable	True
Suitable for solid core	False
Type of connector	RJ45 8(8)
Type of locking	Crimp
screened	True

Available variants

ArtNr.	Bezeichnung	Colour
37641.S	TM21DP-TM-88P(61) CAT6 Connector,TM21	transparent

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

