


DATASHEET

Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL7035 grey



Class E



General data

The high quality of the shielded Cat.6 RJ45 patch panel ensures excellent performance for 5 Gigabit Ethernet applications.

19" mounting, 1U

24 Ports

LSA connection strip for installation cable AWG24..AWG22

Color code according to TIA / EIA 568 A / B

Lid with quick release

With earthing terminal

Scope of delivery:

24 cable ties, Instruction manual, 4 screw M6x18mm with nuts

Technical properties

Bandwidth	250 MHz
Category	6
Colour Code	acc. to TIA/EIA 568A/B
Complaint to UL94	V-0
Connection type	LSA

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.



DATASHEET

Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL7035 grey

Contact Resistance	100 mΩ
Contact coating	gold plated μ" gold plated
Cross section	AWG 24 - AWG 22
Current capacity	1.5 A
Depth	108.0 mm
Dielectric Withstanding Voltage	750 V AC 60Hz
Durability LSA contacts	200
Earthing wire	4 mm ²
Electrical strength	125 V AC RMS
Height	44.5 mm
Housing material LSA-terminal	PC
Housing material Panel	Steel. 1.5mm
Housing material of RJ45 jacks	PBT
Insertion force	50 N
Insulation Resistance	1000 MΩ
Material LSA contacts	Phosphor bronze, tinned
Mating cycles RJ45 jack	750
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
POE Standard	4PPoE
Temperature Range (Operation)	0 – 70 °C
Transmission	5 Gbit
Type of connector	RJ45 8(8)
Width	482.6 mm
screened	True

Available variants

ArtNr.	Bezeichnung	Colour	Number of buses/couplings	RAL-number
37667.1M	Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL7035 grey	grey	24	7035
37667SW.1M	Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL9005 black	schwarz	24	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

