


DATASHEET

Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL9005 black



Class E



General data

The black, shielded patch panel STP 24xRJ45 Cat.6, 19" 1U from EFB-Elektronik ensures structured and low-interference network cabling in the 19-inch rack. With 24 RJ45 sockets and 1U height, it is designed for compact installation in professional distribution environments.

- 24 RJ45 jacks on 1U – Creates a compact patch panel solution for clear distributions in a 19-inch rack.
- Category 6 with 250 MHz – Provides the basis for transmissions up to 5 Gbit and solid reserves in network operation.
- Shielded design with LSA and AWG 24 to AWG 22 – Supports low-interference installation and precise termination in structured cabling.

The connector type RJ45 8(8) and the LSA connection type are designed for use in professional network environments. The shielded design reduces interference and supports stable signal paths. With the mounting type for 482.6 mm (19 inches) installation and the compact height of 1 U, the patch panel can be integrated in a space-saving manner. The black version in RAL 9005 blends inconspicuously into existing system environments.

Technical details

- Brand: EFB-Elektronik
- Number of bushings/couplings: 24
- Number of height units (U): 1U
- Connector type: RJ45 8(8)
- Connection type: LSA

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL9005 black

- Category: 6
- Transmission: 5 Gbit
- Bandwidth: 250 MHz
- Shielded: Yes
- Cross-section: AWG 24 - AWG 22
- Mounting type: 482.6 mm (19 in) Installation
- Colour: black
- RAL number: 9005

Technical properties

Bandwidth	250 MHz
Category	6
Colour Code	acc. to TIA/EIA 568A/B
Complaint to UL94	V-0
Connection type	LSA
Contact Resistance	100 mΩ
Contact coating	gold plated μ" gold plated
Cross section	AWG 24 - AWG 22
Current capacity	1.5 A
Depth	108.0 mm
Dielectric Withstanding Voltage	750 V AC 60Hz
Durability LSA contacts	200
Earthing wire	4 mm ²
Electrical strength	125 V AC RMS
Height	44.5 mm
Housing material LSA-terminal	PC
Housing material Panel	Steel. 1.5mm
Housing material of RJ45 jacks	PBT
Insertion force	50 N
Insulation Resistance	1000 MΩ
Material LSA contacts	Phosphor bronze, tinned
Mating cycles RJ45 jack	750
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
POE Standard	4PPoE
Temperature Range (Operation)	0 – 70 °C
Transmission	5 Gbit
Type of connector	RJ45 8(8)
Width	482.6 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL9005 black

screened

True

Available variants

ArtNr.	Bezeichnung	Colour	Number of buses/couplings	RAL-number
37667.1M	Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL7035 grey	grey	24	7035
37667SW.1M	Patchpanel STP 24xRJ45 Cat.6, 19" 1U, RAL9005 black	black	24	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

