DATASHEET

YV 2 x 0.6/1.1 white-blue, Ring a 100 m

General data	
Other types on request	
Technical properties	
Armouring	False
Circuit integrity	False
Conductor category	Class 1 = solid
Core identification	Colour
Core insulation	PVC
Diameter conductor	0.6 mm
Flame retardant	acc. to EN 60332-1-2
Halogen free (acc. EN 50267-2-2)	False
Longitudinal water blocking	False
Low smoke (acc. EN 61034-2)	False
Material outer sheath	-
Number of stranding elements	2
Operating temperature, fix	70 – °C
Operating temperature, flexible	70 – °C
Outdoor use permitted	False
Protective sheath	False
Radial water blocking	False
Screen over stranding	None
Screen over stranding element	without
Stranding	-

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

YV 2 x 0.6/1.1 white-blue, Ring a 100 m

Stranding element	Pairs

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Number of cores	Outer diameter approx.
46100.100	YV 2 x 0.6/1.1 white-blue, Ring a 100 m	white/blue	2	1.1 mm
46102.100	YV 2 x 0.6/1.1 white-green, Ring a 100 m	white/green	2	1.1 mm
46104.100	YV 2 x 0.6/1.1 white-black, Ring a 100 m	white/black	2	1.1 mm
46107.100	YV 2 x 0.6/1.1 white-yellow Ring a 100 m	white/yellow	2	1.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION