

DATASHEET

YV 2 x 0.6/1.1 white-yellow Ring a 100 m



General data

Other types on request

Technical properties

Armouring	False
Circuit integrity	False
Conductor category	Class 1 = solid
Core identification	Colour
Core insulation	PVC
Diameter conductor	0.6 mm
Flame retardant	acc. to EN 60332-1-2
Halogen free (acc. EN 50267-2-2)	False
Longitudinal water blocking	False
Low smoke (acc. EN 61034-2)	False
Material outer sheath	-
Number of stranding elements	2
Operating temperature, fix	70 - °C
Operating temperature, flexible	70 - °C
Outdoor use permitted	False
Protective sheath	False
Radial water blocking	False
Screen over stranding	None
Screen over stranding element	without
Stranding	-

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

YV 2 x 0.6/1.1 white-yellow Ring a 100 m

Stranding element

Pairs

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Number of cores	Outer diameter approx.
46100.100	YV 2 x 0.6/1.1 white-blue, Ring a 100 m	white/blue	2	1.1 mm
46102.100	YV 2 x 0.6/1.1 white-green, Ring a 100 m	white/green	2	1.1 mm
46104.100	YV 2 x 0.6/1.1 white-black, Ring a 100 m	white/black	2	1.1 mm
46107.100	YV 2 x 0.6/1.1 white-yellow Ring a 100 m	white/yellow	2	1.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

