

DATASHEET

LSA Overvoltage Arrester 8x6 / 230 V / 10 kA



General data

Gas-filled
Rated discharge current 10 kA

Technical properties

Connection 1	terminal
Explosion-tested version	False
Mounting method	LSA-plus plugin
Signalling at the device	Without
With remote signalling contact	False

Available variants

ArtNr.	Bezeichnung	Frequency	Nominal discharge surge current (8/20)	Nominal load current	Nominal voltage AC	Nominal voltage DC	Pro-active thermo-control	Type
46142.1	LSA Overvoltage Arrester 8x6 / 90 V / 10 kA	3 Hz	10 kA	10000 A	90.0 V	90 V	True	8x6 / 90V / 10kA
46143.1	LSA Overvoltage Arrester 8x6 / 230 V / 10 kA	3 Hz	10 kA	10000 A	250 V	230 V	True	8x6 / 230V / 10kA
46144.1	LSA Overvoltage Arrester 8x6 / 230 V / 10 kA + FailSafe	3 Hz	10 kA	10000 A	250 V	230 V	True	8x6 /230V / 10kA + Failsave

This datasheet was created automatically on 12-10-2026 . Technical changes reserved.



DATASHEET

LSA Overvoltage Arrester 8x6 / 230 V / 10 kA

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-10-2026 . Technical changes reserved.

