


DATASHEET

Adapter ST Simplex OS2 metal housing



General data

ST Simplex Adapter with Metal Housing

Technical properties

Accessories	Metric Bold
Colour Dust Cover	Blue
Conform to Standard	IEC61754-2
Construction type	SC-Simplex
Dust cover	True
Height	11.2 mm
Internal Shutter	False
Length	29.2 mm
Material housing	metal
Material sleeve	Ceramics
Operating temperature	-40 - 75 °C
Packaging	Polybag
Scope of deliveryLieferumfang	1 coupling, 2 screws
Storage Temperature	-40 - 85 °C

This datasheet was created automatically on 06-10-2026 . Technical changes reserved.



DATASHEET

Adapter ST Simplex OS2 metal housing

Type of connector connection 1	ST
Type of connector connection 2	ST
Type of fastening	Screw
Type of housing	flangeless
Type of locking	Bayonet locking mechanism
Width	11.2 mm

Available variants

ArtNr.	Bezeichnung	Category	Colour	Insertion loss 1310nm	Model	Suitable for type of fibre
53103.3	Adapter ST Simplex OS2 metal housing	OS2	metall	< 0,2 dB	ST	Single mode

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 06-10-2026 . Technical changes reserved.

