

DATASHEET

Connector ST-II MM 3.0mm Connector (Metall) Boot (with-out)



General data

ST-II connector Simplex Multimode

Technical properties

Connection type	Crimping
Durability	< 0.2db at 500 connection cycles
Inner diameter of the ferrule	127 µm
Material of ferrule	Circonia
Model	Plug
Operating temperature	-40 - 75 °C
Packaging	Polybag
Scope of delivery	1x ST-II Connector Kit
Storage Temperature	-40 - 75 °C
Type of connector	ST-II

Available variants

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

DATASHEET

Connector ST-II MM 3.0mm Connector (Metall) Boot (without)

ArtNr.	Bezeichnung	Anti-kink sleeve	Cable Ø	Colour	Suitable for type of fibre	Ferrule angle	Ferrule outer diameter	Typ. insertion Loss	Max. insertion Loss	Ferrule inner diameter	Return Loss
53202.3	Connector ST-II MM 3.0mm Connector (Metall) Boot (without)	no boot	3 mm	metall	Multi mode	0° UPC	2.5 mm	≤0.20 dB	≤0.30 dB	125 µm	≥35 dB

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

