

DATASHEET

Boot ST/SC black 0.9mm



General data

The ST/SC black glass fibre protection grommet from EFB-Elektronik is designed for ST and SC connectors and is intended for fibre optic cables with a cable diameter of 0.9 mm. The black version supports clean and uniform integration into corresponding installations.

- Intended for ST and SC connectors – Supports the protected routing of fibre optic cables at matching connectors.
- Suitable for 0.9 mm diameter cables – Ensures a fitting fit of the strain-relief boot and makes installation easier.
- Black version with black strain-relief boot – Enables discreet and uniform implementation in the installation environment.

The structure of the strain-relief boot grommet is adapted to a cable diameter of 0.9 mm. The black strain-relief boot complements the black grommet and supports clean installation on ST and SC connections. The scope of delivery includes 1x ST/SC strain-relief boot.

Technical details

- Variation group: ST/SC strain-relief boot
- Connector type: ST+SC
- Brand: EFB-Elektronik
- Colour: black
- Cable diameter: 0.9 mm
- Strain-relief boot colour: black
- Scope of delivery: 1x ST/SC strain-relief boot

Technical properties

Operating temperature	-40 – 75 °C
Packaging	Polybag
Scope of delivery	1x ST/SC Boot
Storage Temperature	-40 – 75 °C
Type of connector	ST + SC

Available variants

ArtNr.	Bezeichnung	Anti-kink sleeve	Cable Ø Colour Grommet length
--------	-------------	------------------	-------------------------------

This datasheet was created automatically on 24-10-2026 . Technical changes reserved.



DATASHEET

Boot ST/SC black 0.9mm

53202.31	Boot ST/SC black 0.9mm	black	0.9 mm	Black	26.0 mm
53202.32	Boot ST black 3.0mm	black	3.0 mm	Black	37.5 mm
53202.33	Boot ST red 3.0mm	red	3.0 mm	red	37.5 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-10-2026 . Technical changes reserved.

