


DATASHEET

Senko Connector SC MM 3.0mm Connector (beige) Boot (black)



General data

The Senko SC Fibre Optic Connector in Beige is designed for multimode applications and is intended for crimp mounting. It is used to manufacture and connect fibre optic cables and is designed for clean, standardised processing.

- Multimode design for SC applications – Supports typical optical links with matching fibre type and is suitable for common multimode installations.
- Connector design with crimp connection type – Enables defined mounting and ensures a reproducible connection of the fibre optic cable.
- Ferrule with PC and full scope of delivery – Supports optical coupling and facilitates direct mounting including matching strain-relief boot.

The design of the connector is based on an SC design in connector design with crimp connection type. The ferrule is made of PC. The design is intended for cables with a diameter of 3 mm. The beige connector is complemented by a black strain-relief boot grommet. This supports clean assembly and mechanical protection of the assembly.

Technical details

- Connector type: SC
- Type: Plug
- Connection type: Crimping

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Senko Connector SC MM 3.0mm Connector (beige) Boot (black)

- Suitable for fibre type: Multimode
- Cable Ø: 3 mm
- Ferrule angle: PC
- Brand: Senko
- Colour: beige
- Strain-relief boot colour: black
- Scope of delivery: 1x SC plug set, 1x SC strain-relief boot

Technical properties

Connection type	Crimping
Durability	< 0.2db at 500 connection cycles
Inner diameter of the ferrule	126 µm
Material of ferrule	Circonia
Model	Plug
Operating temperature	-40 – 75 °C
Packaging	Polybag
Scope of delivery	1x SC/APC Connector Kit, 1x SC Boot
Storage Temperature	-40 – 75 °C
Type of connector	SC/APC

Available variants

ArtNr.	Bezeichnung	Anti-kink sleeve	Cable Ø	Colour	Suitable for type of fibre	Ferrule angle	Grommet length	Ferrule outer diameter	Typ. insertion Loss	Max. insertion Loss	Ferrule inner diameter	Return Loss
53206.11	Senko Connector SC MM 3.0mm Connector (beige) Boot (black)	black	3.0 mm	beige	Multi mode	0° UPC	28.0 mm	2.5 mm	≤0.15 dB	≤0.30 dB	127 µm	≥25 dB
53206.12	Senko Connector SC MM 3.0mm Connector (beige) Boot (red)	red	3.0 mm	beige	Multi mode	0° UPC	28.0 mm	2.5 mm	≤0.15 dB	≤0.30 dB	127 µm	≥25 dB
53206.21	Senko Connector SC MM 2.0mm Connector (beige) Boot (black)	black	2.0 mm	beige	Multi mode	0° UPC	28.0 mm	2.5 mm	≤0.15 dB	≤0.30 dB	127 µm	≥25 dB

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Senko Connector SC MM 3.0mm Connector (beige) Boot (black)

53206.22	Senko Connector SC MM 2.0mm Connector (beige) Boot (red)	red	2.0 mm	beige	Multi mode	0° UPC	28.0 mm	2.5 mm	≤0.15 dB	≤0.30 dB	127 µm	≥25 dB
53213.2	Senko Connector SC SM 3.0mm Connector (blue) Boot (blue)	blue	3.0 mm	blue	Single mode	0° UPC	28.0 mm	2.5 mm	≤0.12 dB	≤0.30 dB	125.5 µm	≥55 dB
53214.1	Senko Connector SC/APC SM 2.0 mm Connector (green) Boot (green)	green	3.0 mm	Green	Single mode	8° APC	28.0 mm	2.5 mm	≤0.08 dB	≤0.20 dB	125.5 µm	≥55 dB
53214.2	Senko Connector SC/APC SM 3.0mm Connector (green) Boot (green)	green	3.0 mm	Green	Single mode	8° APC	28.0 mm	2.5 mm	≤0.08 dB	≤0.20 dB	125.5 µm	≥55 dB

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

