DATASHEET

Connector FC MM 3.0mm Connector (Metall) Boot (black)



General data

High-quality FC connector from EFB-Elektronik in metal design for the production and connection of fibre optic cables. The connector is designed for multimode applications and designed for use in optical connections.

• Suitable for multimode fibre applications – Supports use in matching optical links and is aimed at typical multimode installations.
• FC connector type in connector type with crimp connection type – Enables standardised connection of fibre optic cables and supports clean assembly.
• Ferrule with PC and scope of delivery as a plug set including strain-relief boot – Supports optical coupling and facilitates the complete assembly of the assembly.

The connector is based on a crimp connection type and a ferrule with PC. The design is intended for cables with a diameter of 3 mm. The metallic connector is supplemented by a black strain-relief boot. This supports clean assembly and mechanical protection of the assembly.

Technical details
• Connector type: FC
• Type: Plug
• Connection type: Crimping
• Suitable for fibre type: Multimode
• Cable diameter: 3 mm
• Ferrule angle: PC
• Brand: EFB-Elektronik
• Colour: metal
• Strain-relief boot colour: black
• Scope of delivery: 1x FC plug set. 1x FC strain-relief boot

Technical properties

Connection type	Crimping
Durability	< 0.2db at 500 connection cycles
Inner diameter of the ferrule	127 µm
Material of ferrule	Circonia
Model	Plug
Operating temperature	-40 – 75 °C
Packaging	Polybag
Scope of delivery	1x FC Connector Kit, 1x FC Boot

This datasheet was created automatically on 28-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Connector FC MM 3.0mm Connector (Metall) Boot (black)

Storage Temperature	-40 – 75 °C
Type of connector	FC

Available variants

ArtNr.	Bezeichnung	Anti-kink sleeve	Cable Ø	Colour	Suitable for type of fibre	Ferrule angle	Ferrule outer diameter	Typ. insertion Loss	Max. insertion Loss	Ferrule inner diameter	Return Loss		
53216.3	Connector FC MM 3.0mm Connector (Metall) Boot (black)	black	3.0 mm	metall	Multi mode	0° UPC	2.5 mm	≤0.20 dB	≤0.30 dB	125 µm	≥35 dB		
53216.4	Connector FC MM 2.0mm Connector (Metall) Boot (red)	red	2.0 mm	metall	Multi mode	0° UPC	2.5 mm	≤0.20 dB	≤0.30 dB	125 µm	≥35 dB		
53227.3	Senko Connector FC SM 3.0mm Connector (Metall) Boot (black)	black	3.0 mm	metal/blue	OS2	Single mode	0° UPC	28.0 mm	2.5 mm	≤0.08 dB	≤0.20 dB	125 µm	≥55 dB
53227.4	Senko Connector FC SM 3.0mm Connector (Metall) Boot (red)	red	3.0 mm	metal/blue	OS2	Single mode	0° UPC	28.0 mm	2.5 mm	≤0.08 dB	≤0.20 dB	125 µm	≥55 dB
53227.5	Senko Connector FC/APC SM 3.0mm Connector (Metall) Boot (green)	green	3.0 mm	metal/green	OS2	Single mode	8° APC	28.0 mm	2.5 mm	≤0.07 dB	≤0.15 dB	125 µm	≥65 dB

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 28-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION