

DATASHEET

Connector FC MM 3.0mm Connector (Metall) Boot (black)



General data

FC plug set different versions

Technical properties

Connection type	Crimping
Durability	< 0.2db at 500 connection cycles
Inner diameter of the ferrule	127 µm
Material of ferrule	Circonia
Model	Plug
Operating temperature	-40 - 75 °C
Packaging	Polybag
Scope of delivery	1x FC Connector Kit. 1x FC Boot
Storage Temperature	-40 - 75 °C
Type of connector	FC

Available variants

ArtNr.	Bezeichnung	Anti-kink sleeve	Cable Ø	Colour	Suitable for type of fibre	Ferrule angle	Ferrule outer diameter	Typ. insertion Loss	Max. insertion Loss	Ferrule inner diameter	Return Loss		
53216.3	Connector FC MM 3.0mm Connector (Metall) Boot (black)	black	3 mm	metall	Multi mode	0° UPC	2.5 mm	≤0.20 dB	≤0.30 dB	125 µm	≥35 dB		
53216.4	Connector FC MM 2.0mm Connector (Metall) Boot (red)	red	2 mm	metall	Multi mode	0° UPC	2.5 mm	≤0.20 dB	≤0.30 dB	125 µm	≥35 dB		
53227.3	Senko Connector FC SM 3.0mm Connector (Metall) Boot (black)	black	3 mm	metal/blue	OS2	Single mode	0° UPC	28.0 mm	2.5 mm	≤0.08 dB	≤0.20 dB	125 µm	≥55 dB

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Connector FC MM 3.0mm Connector (Metall) Boot (black)

53227.4	Senko Connector FC SM 3.0mm Connector (Metall) Boot (red)	red	3 mm	metal/blue	OS2	Single mode	0° UPC	28.0 mm	2.5 mm	≤0.08 dB	≤0.20 dB	125 µm	≥55 dB
53227.5	Senko Connector FC/APC SM 3.0mm Connector (Metall) Boot (green)	green	3 mm	metal/green	OS2	Single mode	8° APC	28.0 mm	2.5 mm	≤0.07 dB	≤0.15 dB	125 µm	≥65 dB

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

