



DATASHEET

Adapter ST Duplex OS2 metal housing



General data

- With 2 M2 x 10 screws
- Hole pattern: SC duplex

Technical properties

Accessories	Metric Bold
Colour Dust Cover	Yellow
Conform to Standard	IEC61754-2
Construction type	SC-Duplex
Dust cover	True
Height	9.4 mm
Internal Shutter	False
Length	30.5 mm
Material housing	metal
Material sleeve	Ceramics
Operating temperature	-40 - 75 °C
Packaging	Polybag
Scope of deliveryLieferumfang	1 coupling, 2 screws

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.



DATASHEET

Adapter ST Duplex OS2 metal housing

Storage Temperature	-40 – 85 °C
Type of connector connection 1	ST-Duplex
Type of connector connection 2	ST-Duplex
Type of fastening	Screw
Type of housing	With flange
Type of locking	Screw lock
Width	34.7 mm

Available variants

ArtNr.	Bezeichnung	Category	Colour	Insertion loss 1310nm	Model	Suitable for type of fibre
53313.34	Adapter ST Duplex OS2 metal housing	OS2	metall	< 0,2 dB	ST	Single mode

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

