

DATASHEET

Wall distributor splice housing W=430 x H=330 x D=100mm, without panels



General data

Housing with two swing doors, lockable,
2 different locks with 2 keys each
With 2 cable entry openings at the top and bottom
for PG16 plus 2 cable entry openings
with sealing strip
Additional strain relief clamps and guides
for fiber and cable storage for fastening
with cable ties. Max. 5 splice cassettes and one
Distributor plate can be mounted.
Up to 6 Pro splice cassettes can be mounted
The distribution plate is fastened in two ways
M3 screws.
Dimensions (W) x (H) x (D) 430 x 330 x 100 mm
Sheet steel 1.2 mm, weight approx. 4.6 kg

Technical properties

Depth	100 mm
Height	330 mm
Mounting method	Wall mounting

This datasheet was created automatically on 25-10-2026 . Technical changes reserved.



DATASHEET

Wall distributor splice housing W=430 x H=330 x D=100mm, without panels

Suitable for number of module inserts	5
Width	430 mm
With front plate	False
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	RAL-number
53604.1V2	Wall distributor splice housing W=430 x H=330 x D=100mm, without panels	grey	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-10-2026 . Technical changes reserved.

