

DATASHEET

DIN Rail Box Housing Empty, without front panel



General data

Fully assembled metal housing
For DIN Rail mounting
Cable entries top/bottom, prepared for M20
Delivery incl. screws for front panel

Included: 1 x splice distributor housing

1x splice cassette

1 x splice holder for 12 crimp splices (Attach of an optional additional splice holder only with double-sided adhesive tape)

1 x cable gland M20

1 x Alu DIN Rail clip

Delivery unassembled and without Front panel

Dimensions: 61x115x113mm

Technical properties

Depth	113.0 mm
Height	115.0 mm
Mounting method	DIN rail (top hat rail)
Temperature Range (Operation)	-40 - 75 °C

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

DATASHEET

DIN Rail Box Housing Empty, without front panel

Temperature Range (Storage)	-40 – 85 °C
Width	61.0 mm
With front plate	False
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	Suitable for number of couplings/adapters	RAL-number
53705.1V3	DIN Rail Box Housing Empty, without front panel	grey	12	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

