



DATASHEET

INFRALAN® U-DQ(ZN)BH OM3 4G (1x4) Dca 1750N LSZH
black 7.0mm



General data

Application:
 For fixed installation indoor and outdoor
 In cable ducts, tubes and interconnections
 Mechanical installation by winch is permitted only when using force meters with recording function
 Not suitable for underground laying (direct buried)

Characteristics:
 Universale cable
 Suitable for connector assembly

The cable diameter can vary

Technical properties

Application	Inside/outside
Armouring	True
Blow in	False
Cable metal free	True
Cable silicone free	True
Circuit integrity	False
Colour outer sheath	black

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.



EFB-Elektronik GmbH
 Striegauer Straße 1
 33719 Bielefeld

fon: +49 521 40 41 8-0
 fax: +49 521 40 41 8-50

info@efb-elektronik.de
 www.efb-elektronik.de

DATASHEET

INFRALAN® U-DQ(ZN)BH OM3 4G (1x4) Dca 1750N LSZH black 7.0mm

Crush resistance	1500 N/dm
Fiber Colours	white
Fiber marking	Colour
Fibre category	OM3
Fibre type	Multi mode 50/125
Flame retardant	acc. to EN 60332-3-24
Halogen free	acc. to EN 60754-1/2
Harmonised Standard	EN 50575
IL max. (dB/km) 1300nm	0.7 dB/km
IL max. (dB/km) 850nm	2.5 dB/km
Longitudinal water blocking	True
Low smoke	True
Low smoke (acc. EN 61034-2)	True
Material outer sheath	LSZH
Oil resistant	no
Oil resistant (acc. EN 60811-2-1)	False
Radial water blocking	True
Rayleigh Backscatter Coefficient 1300nm	1.478
Rayleigh Backscatter Coefficient 850nm	1.483
Resistant to chemicals	False
Scope of delivery	1x Cable1x Drum
Temperature Range (Installation)	-5 - 50 °C
Temperature Range (Operation)	-20 - 60 °C
Temperature Range (Storage)	-25 - 70 °C
Tube marking	Colour
Tube Ø	3.5 mm
Type of tube	Central tube
UV resistant	True
With rodent protection	True
With strain relief	True

Available variants

ArtNr.	Bezeichnung	CPR-Class	Cable Ø	Category of fibres	Number of fibres	Tensile force max.	Number of fibres per tube	Suitable for Construct underground installation	Outer diameter approx.	Fire load	Minimum bending radius (dynamic)	VDE-Name	Weight	Minimum bending radius (static)
--------	-------------	-----------	------------	-----------------------	---------------------	--------------------------	---------------------------------------	---	------------------------------	--------------	---	----------	--------	--

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.



DATASHEET

INFRALAN® U-DQ(ZN)BH OM3 4G (1x4) Dca 1750N LSZH black 7.0mm

54504.1L-CPR	INFRALAN® U-DQ(ZN)BH OM3 4G (1x4) Dca 1750N LSZH black 7.0mm	Dca	7.0 mm	OM3	4	1750 N	4	(1x4)	True	7.0 mm	0.71 MJ/m	20xOD mm	U-DQ(ZN)BH 4G50/125	55 kg/km	15xOD mm
54508.1L-CPR	INFRALAN® U-DQ(ZN)BH OM3 8G (1x8) Dca 1750N LSZH black 7.0mm	Dca	7.0 mm	OM3	8	1750 N	8	(1x8)	True	7.0 mm	0.71 MJ/m	20xOD mm	U-DQ(ZN)BH 8G50/125	55 kg/km	15xOD mm
54512.1L-CPR	INFRALAN® U-DQ(ZN)BH OM3 12G (1x12) Dca 1750N LSZH black 7.0mm	Dca	7.0 mm	OM3	12	1750 N	12	(1x12)	True	7.0 mm	0.71 MJ/m	20xOD mm	U-DQ(ZN)BH 12G50/125	55 kg/km	15xOD mm
54524.1L-CPR	INFRALAN® U-DQ(ZN)BH OM3 24G (1x24) Dca 1750N LSZH black 7.5mm	Dca	7.5 mm	OM3	24	1750 N	24	(1x24)	True	7.5 mm	0.79 MJ/m	20xOD mm	U-DQ(ZN)BH 24G50/125	55 kg/km	15xOD mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.

