

DATASHEET

INFRALAN® U-DQ(ZN)BH OM3 12G (1x12) Eca 3000N LSZH black 7.5mm













General data

Fiber optic cable with a central gel-filled loose tube and up to 24 fibers, ideal for structured cabling.
With a tensile strength of 3000N, it is suitable for both indoor and outdoor applications. The dielectric design includes a glass yarn armor that is longitudinally watertight and rodent-proof, as well as a flame-retardant jacket.
This cable is versatile for LAN and WAN backbones, telecom access lines, fiber-to-business, fiber-to-the-home and access connections.
It can be used outdoors, for direct burial in sand beds or in shafts, and as a flame-retardant cable indoors.

Features:
• Universal cable for versatile applications
• High tensile strength of 3000N for robust applications
• The jacket is made of halogen-free, flame-retardant material according to IEC 60332-1-2 and Eurofire class Eca.

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

INFRALAN® U-DQ(ZN)BH OM3 12G (1x12) Eca 3000N LSZH black 7.5mm

- Suitable for connector assemblies, supports easy integration into existing networks
- Metal-free and longitudinally watertight
- Rodent-proof and flame-retardant
- The cable diameter can vary depending on the design and number of fibers
- DIN/VDE: U-DQ(ZN)BH

Technical properties	
Application	Inside/outside
Armouring	True
Blow in	False
Cable metal free	True
Cable silicone free	True
Circuit integrity	False
Colour outer sheath	black
Crush resistance	3500 N/dm
Fiber Colours	white
Fiber marking	Colour
Fibre category	OM3
Fibre type	Multi mode 50/125
Flame retardant	acc. to EN 60332-1-2
Halogen free	acc. to EN 60754-1/2
Harmonised Standard	EN 50575
IL max. (dB/km) 1300nm	1.0 dB/km
IL max. (dB/km) 850nm	3.0 dB/km
Longitudinal water blocking	True
Low smoke	True
Material outer sheath	LSZH
Oil resistant	no
Radial water blocking	True
Resistant to chemicals	False
Scope of delivery	1x Cable, 1x Drum
Temperature Range (Installation)	-15 – 60 °C
Temperature Range (Operation)	-30 – 70 °C
Temperature Range (Storage)	-30 – 60 °C
Tube marking	Colour
Tube Ø	2.8 mm
Type of tube	Central tube

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

INFRALAN® U-DQ(ZN)BH OM3 12G (1x12) Eca 3000N LSZH black 7.5mm

UV resistant	True
With rodent protection	True
With strain relief	True

Available variants

ArtNr.	Bezeichnung	CPR-Class	Cable Ø	Category	Number of fibres	Tensile force max.	Number of fibres per tube	Construct	Suitable for underground installation	Outer diameter approx.	Fire load	Minimum bending radius (dynamic)	VDE-Name	Weight	Minimum bending radius (static)
54504D1E-CPR	INFRALAN® U-DQ(ZN)BH OM3 4G (1x4) Eca 3000N LSZH black 7.5mm	Eca	7.5 mm	OM3	4	3000 N	4	(1x4)	True	7.5 mm	1285 MJ/km	20xOD mm	U-DQ(ZN)BH 4G50/125	51.7 kg/km	10xOD mm
54512D1E-CPR	INFRALAN® U-DQ(ZN)BH OM3 12G (1x12) Eca 3000N LSZH black 7.5mm	Eca	7.5 mm	OM3	12	3000 N	12	(1x12)	True	7.5 mm	1285 MJ/km	20xOD mm	U-DQ(ZN)BH 12G50/125	51.7 kg/km	10xOD mm
54524D1E-CPR	INFRALAN® U-DQ(ZN)BH OM3 24G (2x12) Eca 3000N LSZH black 7.5mm	Eca	7.5 mm	OM3	24	3000 N	24	(1x24)	True	7.5 mm	1285 MJ/km	20xOD mm	U-DQ(ZN)BH 24G50/125	51.7 kg/km	10xOD mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION