


DATASHEET

I-V(ZN)H Duplex-Zipcord OM3 2G (2x1) 600N LSZH aqua 2.8x5.7mm



General data

Application: Indoor application
 Secondary Cabling (Vertical): Rising Area (Backbone)
 Tertiary cabling (horizontal): working area, fiber-to-the-desk (FTTD)
 Patch- and adapter cable
 Indoor cable
 Non-metallic, halogenfree
 Suitable for field installable connectors

Technical properties

Application	Inside
Armouring	False
Blow in	False
Cable & Fiber	IEC 60794-2
Cable metal free	True
Cable silicone free	True
Circuit integrity	False
Colour outer sheath	aqua
Crush resistance	600 N/dm
Fiber Colours	white
Fiber marking	Colour
Fibre category	OM3
Fibre type	Multimode 50/125
Flame retardant	According to EN 60332-1-2
Halogen free	acc. to EN 60754-1/2
Harmonised Standard	-
IL max. (dB/km) 1300nm	0.8 dB/km
IL max. (dB/km) 850nm	2.7 dB/km
Longitudinal water blocking	False
Low smoke	True
Material outer sheath	LSZH

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.



DATASHEET

I-V(ZN)H Duplex-Zipcord OM3 2G (2x1) 600N LSZH aqua 2.8x5.7mm

Oil resistant	no
Radial water blocking	False
Resistant to chemicals	False
Scope of delivery	1x Cable1x Drum
Temperature Range (Installation)	-5 - 50 °C
Temperature Range (Operation)	-10 - 70 °C
Temperature Range (Storage)	-25 - 70 °C
Tube Ø	2.8 x 5.7 mm
Type of tube	Tight
UV resistant	Nein
With rodent protection	False
With strain relief	True

Available variants

ArtNr.	Bezeichnung	Cable Ø	Category	Number of fibres	Tensile force max.	Number of fibres per tube	Construct	Suitable for underground installation	Outer diameter approx.	Fire load	Minimum bending radius (dynamic)	VDE-Name	Weight	Minimum bending radius (static)
56005.1	I-V(ZN)H Duplex-Zipcord OM3 2G (2x1) 600N LSZH aqua 2.8x5.7mm	2.8 x 5.7 mm	OM3	2	600 N	1	(2x1)	False	2.8 x 5.7 mm	0.36 MJ/m	15xOD mm	I-V(ZN)H 2G50/125	16 kg/km	10xOD mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

