DATASHEET

19" Wall Housing 12U, Swiveling, 2-Part, RAL7035, Depth 600 mm













General data

The 19" swivel, 2-piece design with a depth of 600 mm and RAL 7035 is designed for use in controlled indoor areas. The pre-assembled sheet steel construction with welded frame combines a robust construction with a self-ventilated base for 19-inch installation.

• 12U in 19-inch increments and 600 mm installation depth – Creates a compact installation situation while still providing sufficient space for network and IT components.
• Pre-assembled, swivelling sheet steel construction with fixed frame – Reduces assembly time and simplifies transport and storage.
• Glass door with latch lock and viewing window made of certified safety glass – Enables visual inspection of components and supports safe access.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and a

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

19" Wall Housing 12U, Swiveling, 2-Part, RAL7035, Depth 600 mm

powder-coated surface. The IP20 protection class, the load capacity of 40 kg and the cable entry via roof, floor and rear with 250 x 70 mm each are designed for operation in indoor areas with clearly defined environmental conditions. The maximum distance of the 19" levels of 415 mm and the installation depth of 550 to 600 mm support a clean integration of the components.

Technical details
- Number of doors: 1
- Degree of protection: IP20
- Type of ventilation: passive
- Mounting level: front
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, not openable
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Replaceable profile half-cylinder in front door: optional (compact swing handle item no. 699989)
- Scope of delivery: 1x cabinet, 1x brush strip, 1x cage nut set (pack of 20 pcs.), 2x wrench
- Packaging: Supplied in transport packaging, from 30 kg / 12 U on a one-way pallet
- Width: 600 mm
- Height: 600 mm
- Depth: 600 mm
- Installation depth min. - max.: 550 mm
- Cable entry roof/floor: roof + floor + 2 x back, each 250 x 70 mm
- Max. distance of the 19" planes: 415 mm
- Payload: 40 kg
- Material: Steel
- Finish of the surface: powder-coated
- RAL number: 7035
- Pitch: 482.6 mm (19 inches)
- Number of rack units (U): 12 U

Technical properties	
Cabinet Series	19" Wall Housing 2-Part, pre-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 250 x 70 mm
Degree of protection	IP20
Demountable	False
Door hinge reversible front door	Yes, by rotating the case 180°
Frame	welded
Installation depth min. - max.	450 mm
Material	Steel
Max. spacing of the 19" levels	415 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing 12U, Swiveling, 2-Part, RAL7035, Depth 600 mm

Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	Delivery in transport packaging, from 30 kg / 12 U on a disposable pallet
Scope of delivery	1x Cabinet, 1x brush strip, 1x cage nut set (Pack size 20 pieces), 2x keys
Structure/Use	Steel sheet housing with welded frame, pre-assembled, self-ventilated.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691606VGR.60	19" Wall Housing 6U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	330 mm	40 kg	6 U	600 mm	7035
691609VGR.60	19" Wall Housing 9U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	465 mm	40 kg	9 U	600 mm	7035
691612VGR.60	19" Wall Housing 12U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	600 mm	40 kg	12 U	600 mm	7035
691615VGR.60	19" Wall Housing 15U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	730 mm	50 kg	15 U	600 mm	7035
691618VGR.60	19" Wall Housing 18U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	860 mm	50 kg	18 U	600 mm	7035
691621VGR.60	19" Wall Housing 21U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	997 mm	50 kg	21 U	600 mm	7035

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing 12U, Swiveling, 2-Part, RAL7035, Depth 600 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION