

DATASHEET

19" 1U Socket Strip 9 x CEE7/3 without Switch, Black



General data

35° turned socket inserts in the aluminium profile
 Cable H05VV-F 3G 1.5 mm², black, 2.0 m, 250 V AC / 16 A with angled CEE7/3 plug CEE7/7
 Supplied mounting brackets allow any fastening position

Technical properties

Angle rotated central insert	35° °
Colour of power cord	black
Core cross section	1.50 mm ²
Degree of protection	IP20
Halogen free	No
Housing shape	Rectangular
Length of power cord	2.0 m
Mains filter	False
Material	Metal
Material quality	Aluminium Aluminium
Max. connected load	3600 W
Mounting dimension (standardised)	465 mm
Nominal current	16 A

This datasheet was created automatically on 06-09-2026 . Technical changes reserved.



DATASHEET

19" 1U Socket Strip 9 x CEE7/3 without Switch, Black

Nominal voltage	230 V
Number of height units (U)	1 U
Number of phases	1
Over voltage protection	False
Packaging	Polybag
Residual current circuit breaker (RCCB)	False
Rotated central insert	True
Scope of delivery	1 x power strip incl. mounting brackets
Surface finishing	Matt
Surface treatment	Anodised
Transparent	False
Type of mains connection	CEE 7/7
With cover lid	False

Available variants

ArtNr.	Bezeichnung	Anti-bacterial treatment	Colour	Compatible with Amazon Alexa	Compatible with Apple HomeKit	Compatible with Google Assistant	IFTTT support available	Number of socket outlets with protective switch contact (CEE7/3)	With on/off switch	Height	RAL-number (similar)
691683	19" 1U Socket Strip 9 x CEE7/3 without Switch, Black	False	black	False	False	False	False	9	False	44 mm	9005
691685	19" 1U Socket Strip 9 x CEE7/3 without Switch, Grey	False	grey	False	False	False	False	9	False	44 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 06-09-2026 . Technical changes reserved.

