

DATASHEET

19" 1U Socket Strip 8 x CEE 7/3 with Switch, RAL7035



General data

Socket Strip PROFiversal 8-way with illuminated switch
 45° turned socket inserts in aluminium profile
 Cable 2.0 m grey, H05VV-F 3G 1.5 mm², 250 V AC / 16 A with angled CEE7/7 plug, rewirable
 Included metal brackets allow any fastening position
 VDE certified

Technical properties

Angle rotated central insert	45°
Colour of power cord	grey
Core cross section	1.50 mm ²
Degree of protection	IP20
Halogen free	No
Housing shape	Rectangular
Length of power cord	2.0 m
Mains filter	False
Material	Metal
Material quality	Aluminium Aluminium
Max. connected load	3680 W
Mounting dimension (standardised)	465 mm
Nominal current	16 A
Nominal voltage	250 V
Number of height units (U)	1 U
Number of phases	1
Over voltage protection	False
Packaging	cardboard box

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.



DATASHEET

19" 1U Socket Strip 8 x CEE 7/3 with Switch, RAL7035

Residual current circuit breaker (RCCB)	False
Rotated central insert	True
Scope of delivery	1 x power strip incl. mounting brackets
Surface finishing	Matt
Surface treatment	Anodised
Transparent	False
Type of mains connection	CEE 7/7
With cover lid	False

Available variants

ArtNr.	Bezeichnung	Anti-bacterial treatment	Colour	Compatible with Amazon Alexa	Compatible with Apple HomeKit	Compatible with Google Assistant	IFTTT support available	Number of socket outlets with protective contact (CEE7/3)	With on/off switch	Height	RAL-number (similar)
691686K	19" 1U Socket Strip 8 x CEE 7/3 with Switch, RAL7035	False	grey	False	False	False	False	8	True	44 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

