


DATASHEET

19" Wall Housing 4U, Fixed, 1-Part, RAL7035, Depth 400 mm



General data

Steel sheet housing with welded frame, completely pre-assembled, self-ventilated

NEW: Prepared for Plug & Play 2-fan unit Art.-No. 691656xx

NEW: Bottom with 4 x mounting point for leveling feet or castor set (please order separately)

NEW: Front door with metal hinges for increased stability

Side walls removable, lockable, locks equal to door lock

Roof, bottom and rear wall with pre-punched openings for cable entry (250 x 70 mm)

Front-sided 2 x 19" profile rails, galvanised, depth-adjustable

Front door with latch locking and window made of certified safety glass (thickness 4 mm)

Internal earthing of all cabinet sections

Paint finish RAL7035, light grey

Protection degree IP20

Included in delivery: 1 x brush terminal, 1 x set of captive nuts (PU 20 pcs.), 2 x key

Delivery in transport packaging, from 30 kg / 12U on disposable pallet

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

DATASHEET

19" Wall Housing 4U, Fixed, 1-Part, RAL7035, Depth 400 mm

Technical properties	
Cabinet Series	19" Wall Housing 1-Part, pre-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 250 x 70 mm
Degree of protection	IP20
Demountable	False
Door hinge reversible front door	Yes
Door opening angle front door	120 °
Frame	welded
Installation depth min. - max.	350 mm
Material	steel sheet
Max. spacing of the 19" levels	315 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	Delivery in transport packaging, from 30 kg / 12 U on a disposable pallet
Scope of delivery	1x Cabinet, 1x brush strip, 1x cage nut set (Pack size 20 pieces), 2x keys
Structure/Use	Steel sheet housing with welded frame, pre-assembled, self-ventilated.
Surface finishing	powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shape
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing 4U, Fixed, 1-Part, RAL7035, Depth 400 mm

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691704VGR.40	19" Wall Housing 4U, Fixed, 1-Part, RAL7035, Depth 400 mm	grey	400 mm	240 mm	50 kg	4 U	600 mm	7035
691706VGR.40	19" Wall Housing 6U, Fixed, 1-Part, RAL7035, Depth 400 mm	grey	400 mm	330 mm	50 kg	6 U	600 mm	7035
691709VGR.40	19" Wall Housing 9U, Fixed, 1-Part, RAL7035, Depth 400 mm	grey	400 mm	465 mm	50 kg	9 HE	600 mm	7035
691712VGR.40	19" Wall Housing 12U, Fixed, 1-Part, RAL7035, Depth 400 mm	grey	400 mm	600 mm	50 kg	12 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

