

DATASHEET

Wall housing 19" 5U vert.+10U hor./10" 10U hor., side wall glass, RAL7035



General data

One Housing - 3 Mounting Options:

19" 5U vertical - 10" 10U horizontal - 19" 10HE horizontal

- Steel sheet housing, completely pre-assembled
- Front door and left side wall with windows of certified safety glass (4 mm)
- Front door lockable with 1-point latch locking
- Left side wall hinged for easy access
- Right side wall with holes for wall mounting
- Rear wall prepared for mounting of plug & play fan unit Art.-No. 691656GR or single fan Art.-No. 691664
- Inner mounting points for earthing set Art.-No. K3930V2N
- Roof and bottom with pre-punched openings for cable entry (145 x 70 mm)
- Paint finish RAL7035, light grey
- Protection degree IP20
- Included in delivery: 1 x brush strip, 1 x plastic cover, 1 x cage nut set (PU 20 pcs.), keys
- Delivery in transport packaging

Technical properties

Cabinet Series	19"+10" Wall Housing Vertical, pre-assembled
Cable entry roof/floor	Roof + base, each 145 x 77 mm

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Wall housing 19" 5U vert.+10U hor./10" 10U hor., side wall glass, RAL7035

Degree of protection	IP20
Demountable	False
Door hinge reversible front door	No
Frame	welded
Installation depth min. - max.	300 / 600 mm
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	2
PHC replaceable front door	No
Packaging	1 carton
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys
Structure/Use	Front door and left side panel with viewing window made of certified safety glass (4 mm). Left side panel folds out. Right side panel with elongated holes for wall mounting. Prepared for the installation of the Plug & Play fan unit, item no. 691656GR.
Surface finishing	powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shape
Type of ventilation	Passive
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Width	RAL-number
691706VGL.1	Wall housing 19" 5U vert.+10U hor./10" 10U hor., side wall glass, RAL7035	grey	682 mm	543 mm	364 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

