DATASHEET

Wall housing 19" 5U vert.+10U hor./10’’ 10U hor., side wall glass, RAL7035







General data

The 19"/10" wall-mounted enclosure from EFB-Elektronik in a grey version according to RAL 7035 is designed for structured installations in technical environments. The pre-assembled construction with fixed frame and welded frame creates a stable base, the powder-coated steel construction is designed for long-term indoor use.

• Vertical 19"/10" combination with 364 mm width and 543 mm height – Creates a compact, well-defined installation situation for network and IT components.
• Fixed frame with welded frame and powder-coated steel construction – Provides a stable base and high dimensional stability during operation.
• Front door with 4 mm viewing window made of certified safety glass and preparation for plug & play fan unit – Enables visual inspection and creates reserves for later active cooling.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and protection class IP20. The cable entry over the roof and floor, each measuring 145 x 77 mm, supports clean cable routing, while the left side wall can be folded out and the right side wall is equipped with slotted holes for wall mounting. The front door is designed as a glass door with latch lock and viewing window made of 4 mm safety glass. The scope of delivery and packaging are designed for a standardised project process.

Technical details

This datasheet was created automatically on 22-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Wall housing 19" 5U vert.+10U hor./10’’ 10U hor., side wall glass, RAL7035

- Number of doors: 2
- Degree of protection: IP20
- Type of ventilation: passive
- Air inlet floor: roof + floor, each 145 x 77 mm
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Scope of delivery: 1x cabinet, 1x brush strip, 1x plastic cover, mounting material, 2x keys
- Packaging: 1 carton

Technical properties	
Cabinet Series	19"+10" Wall Housing Vertical, pre-assembled
Cable entry roof/floor	Roof + base, each 145 x 77 mm
Degree of protection	IP20
Demountable	False
Door hinge reversible front door	No
Frame	welded
Installation depth min. - max.	300 / 600 mm
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	2
PHC replaceable front door	No
Packaging	1 carton
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys
Structure/Use	Front door and left side panel with viewing window made of certified safety glass (4 mm). Left side panel folds out. Right side panel with elongated holes for wall mounting. Prepared for the installation of the Plug & Play fan unit, item no. 691656GR.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped

This datasheet was created automatically on 22-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Wall housing 19" 5U vert.+10U hor./10’’ 10U hor., side wall glass, RAL7035

Type of ventilation	Passive
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Width	RAL-number
691706VGL.1	Wall housing 19" 5U vert.+10U hor./10’’ 10U hor., side wall glass, RAL7035	grey	682 mm	543 mm	364 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION