


DATASHEET

19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL7035



General data

Steel sheet housing with screwed frame
 Not pre-assembled, self-ventilated
 Side wall removable with quick fastener
 Roof, bottom and rear wall with pre-punched openings for cable entry (230 x 41 mm)
 Roof prepared for mounting of 2 x single fan (Art.-No. 691664)
 Inside 2 x 19" rails front-sided, depth-adjustable
 Front door with window of certified safety glass with lock (thickness 4 mm)
 Cabinet parts completely earthed
 Max. load 60 kg
 Protection degree IP20
 Paint finish RAL7035, light grey
 Included accessories: 2 x key
 Delivery unassembled in transport packaging (1 carton)

Technical properties

Cabinet Series	19" Wall Housing FLAT PACK, un-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 230 x 41 mm
Degree of protection	IP20
Demountable	True

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL7035

Door hinge reversible front door	Yes
Frame	screwed together, unassembled
Installation depth min. - max.	530 mm
Material	Steel
Max. spacing of the 19" levels	490 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	1 carton
Scope of delivery	1x Cabinet, grounding cable, 2x keys
Structure/Use	Steel sheet housing with very solid frame, self-ventilated, not pre-assembled.
Surface finishing	powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shape
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691709FGR.2	19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL7035	grey	600 mm	500 mm	60 kg	9 HE	570 mm	7035
691712FGR.2	19" Wall Housing Flat Pack 12U, Depth 600 mm, RAL7035	grey	600 mm	635 mm	60 kg	12 U	570 mm	7035
691715FGR.2	19" Wall Housing Flat Pack 15U, Depth 600 mm, RAL7035	grey	600 mm	770 mm	60 kg	15 U	570 mm	7035
691721FGR.2	19" Wall Housing Flat Pack 21U, Depth 600 mm, RAL7035	grey	600 mm	1040 mm	60 kg	21 U	570 mm	7035

Note on Intended Use

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL7035

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

