


DATASHEET

19" Wall Housing Flat Pack 9U, Depth 450 mm, RAL9005



General data

The 19" Flat Pack wall enclosure in 9U and 450 mm depth in RAL 9005 is designed as a robust solution for demanding interior applications. The unassembled flat pack design facilitates transport and storage, while the bolted frame and sheet steel construction form a stable base for the 19-inch installation.

- 9U in 19-inch format with 450 mm depth - Creates a compact, well-defined installation situation for network and IT components.
- Unassembled flat-pack design with bolted frame - Reduces the hassle of transport, storage and final assembly.
- Front door as a glass door with viewing window made of certified safety glass - Enables visual inspection and combines it with a flexible door hinge solution.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and protection class IP20. The powder-coated steel construction, the load capacity of 60 kg and the cable entries via roof, floor and rear are designed for controlled interior areas and clean integration of the cabling. With earthing, roof panel,

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing Flat Pack 9U, Depth 450 mm, RAL9005

front door and openable, lockable side panels, the basic equipment is designed for practical use.

Technical details

- Number of doors: 1
- Degree of protection: IP20
- Type of ventilation: passive
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Reversible front door hinging: Yes
- Replaceable profile half-cylinder in front door: optional, compact swing handle item no. 699989
- Scope of delivery: 1x cabinet, earthing cable, 2x keys
- Packaging: 1 carton
- Depth: 450 mm
- Height: 500 mm
- Width: 570 mm
- Payload: 60 kg
- Colour: black
- Material: Steel
- Finish of the surface: powder-coated
- Cable entry roof/floor: roof + floor + 2 x back, each 230 x 41 mm
- Frame: bolted, unassembled

Technical properties	
Cabinet Series	19" Wall Housing FLAT PACK, un-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 230 x 41 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, unassembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	1 carton

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

19" Wall Housing Flat Pack 9U, Depth 450 mm, RAL9005

Scope of delivery	1x Cabinet, grounding cable, 2x keys
Structure/Use	Steel sheet housing with very solid frame, self-ventilated, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691706FTS.1	19" Wall Housing Flat Pack 6U, Depth 450 mm, RAL9005	black	450 mm	370 mm	60 kg	6 U	570 mm	9005
691709FTS.1	19" Wall Housing Flat Pack 9U, Depth 450 mm, RAL9005	black	450 mm	500 mm	60 kg	9 U	570 mm	9005
691712FTS.1	19" Wall Housing Flat Pack 12U, Depth 450 mm, RAL9005	black	450 mm	635 mm	60 kg	12 U	570 mm	9005
691715FTS.1	19" Wall Housing Flat Pack 15U, Depth 450 mm, RAL9005	black	450 mm	770 mm	60 kg	15 U	570 mm	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

