
DATASHEET

19" Wall Housing IP55, 9U, Glass Door, Depth 450 mm, RAL7035









General data

The 19" IP55 wall enclosure from EFB-Elektronik in RAL 7035 with a depth of 450 mm is designed for demanding installations in controlled indoor areas. The completely pre-assembled sheet steel construction with welded body facilitates assembly and storage. PUR seals on the roof and door support dust and water protection.

• 9U in 19-inch design with 450 mm depth – Provides a compact and well-defined installation situation for network and IT components.
• Fully pre-assembled sheet steel body with welded frame – Reduces assembly effort and creates a stable base for installation.
• Front door as a one-piece glass door with replaceable profile half-cylinder – Enables visual inspection and supports flexible locking integration.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and an IP55 protection class. The powder-coated surface and the load capacity of 100 kg are designed for stable use. The installation depth is 380 mm. For cable entry, the floor is designed with 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC cable grommets. The maximum distance between the 19" levels is 340 mm.

Technical details
• Number of doors: 1

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing IP55, 9U, Glass Door, Depth 450 mm, RAL7035

- Degree of protection: IP55
- Type of ventilation: passive
- Air inlet bottom: bottom, PG glands 1 x PG48, 2 x PG21, 3 x Ø 20 mm PVC cable grommets
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, not openable
- Mounting level: front
- Front door design: one-piece glass door
- Front door opening angle: approx. 120 °
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 4x wall bracket, 2x keys
- Packaging: 1 carton

Technical properties	
Cabinet Series	19" Wall Housing IP55
Cable entry roof/floor	Floor, PG glands 1 x PG48, 2 x PG21, 3 x Ø 20 mm PVC grommet
Degree of protection	IP55
Demountable	False
Door hinge reversible front door	No
Door opening angle front door	ca. 120 °
Frame	welded
Installation depth min. - max.	380 mm
Material	Steel
Max. spacing of the 19" levels	340 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	Yes, DIN18252 (30/10 mm)
Packaging	1 carton
Scope of delivery	1x Cabinet, 4x wall mount, 2x keys
Structure/Use	Steel sheet housing with welded body, fully pre-assembled. PUR seals on roof and door for dust and water protection.
Surface finishing	Powder coating
Type of front door	Glass door 1-part
Type of profile rail	L-shaped

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing IP55, 9U, Glass Door, Depth 450 mm, RAL7035

Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691707IP55.1G	19" Wall Housing IP55, 7U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	450 mm	100 kg	7 U	600 mm	7035
691709IP55.1G	19" Wall Housing IP55, 9U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	540 mm	100 kg	9 U	600 mm	7035
691712IP55.1G	19" Wall Housing IP55, 12U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	670 mm	100 kg	12 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION