

DATASHEET

19" Wall Housing IP55, 9U, Steel Door, Depth 600 mm, RAL7035



General data

The 19" IP55 wall enclosure in 9 U and 600 mm depth in RAL 7035 is designed for use in demanding indoor areas. The completely pre-assembled sheet steel construction with welded body creates a stable basis for the 19-inch installation. PUR seals on the roof and door support protection against dust and water.

- IP55 rating with PUR seals on roof and door – Supports operation in environments with increased dust and moisture levels and increases operational safety.
- Fully pre-assembled sheet steel construction with welded body – Reduces assembly effort and provides a robust mechanical base for installation.
- One-piece steel door with replaceable profile half-cylinder in accordance with DIN 18252 – Allows access control that can be adapted to the locking system.

In terms of technical design, the housing combines a mounting level at the front and rear with passive ventilation and floor entry. Cable entry via the floor is carried out with PG glands in 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC cable grommets. With a payload of 100 kg, an installation depth of 530 mm and a maximum distance of 490 mm between the 19" levels, the design is designed for a clean integration of network and IT components. The powder-coated surface in grey and the structure with roof panel, earthing and non-openable side panels support a closed and durable design.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing IP55, 9U, Steel Door, Depth 600 mm, RAL7035

Technical details

- Number of doors: 1
- Degree of protection: IP55
- Type of ventilation: passive
- Air inlet bottom: bottom, PG glands 1 x PG48, 2 x PG21, 3 x Ø 20 mm PVC cable grommets
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, not openable
- Mounting level: front and rear
- Front door design: one-piece steel door
- Front door opening angle: approx. 120 °
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 4x wall bracket, 2x keys
- Packaging: 1 carton
- Number of rack units (U): 9 U
- Height: 500 mm
- Width: 600 mm
- Depth: 600 mm
- Installation depth min. - max.: 530 mm
- Max. distance of the 19" levels: 490 mm
- Load capacity: 100 kg
- Material: Steel
- Finish of the surface: powder-coated
- Colour: grey
- RAL number: 7035.0

Technical properties

Cabinet Series	19" Wall Housing IP55
Cable entry roof/floor	Floor, PG glands 1 x PG48, 2 x PG21, 3 x Ø 20 mm PVC grommet
Degree of protection	IP55
Demountable	False
Door hinge reversible front door	No
Door opening angle front door	ca. 120 °
Frame	welded
Installation depth min. - max.	530 mm
Material	Steel
Max. spacing of the 19" levels	490 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing IP55, 9U, Steel Door, Depth 600 mm, RAL7035

Mounting level	Front and rear
Number of cartons	1
Number of doors	1
PHC replaceable front door	Yes, DIN18252 (30/10 mm)
Packaging	1 carton
Scope of delivery	1x Cabinet, 4x wall mount, 2x keys
Structure/Use	Steel sheet housing with welded body, fully pre-assembled. PUR seals on roof and door for dust and water protection.
Surface finishing	Powder coating
Type of front door	Steel door 1-part
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691707IP55.2	19" Wall Housing IP55, 7U, Steel Door, Depth 600 mm, RAL7035	grey	600 mm	410 mm	100 kg	7 U	600 mm	7035
691709IP55.2	19" Wall Housing IP55, 9U, Steel Door, Depth 600 mm, RAL7035	grey	600 mm	500 mm	100 kg	9 U	600 mm	7035
691712IP55.2	19" Wall Housing IP55, 12U, Steel Door, Depth 600 mm, RAL7035	grey	600 mm	630 mm	100 kg	12 U	600 mm	7035
691716IP55.2	19" Wall Housing IP55, 16U, Steel Door, Depth 600 mm, RAL7035	grey	600 mm	810 mm	100 kg	16 U	600 mm	7035
691720IP55.2	19" Wall Housing IP55, 20U, Steel Door, Depth 600 mm, RAL7035	grey	600 mm	1000 mm	100 kg	20 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

