
DATASHEET

19" Wall Housing Flat Pack 12U, Depth 450 mm, RAL7035









General data

The 19" wall enclosure Flat Pack from EFB-Elektronik in RAL 7035 combines 12 U with a depth of 450 mm and an unassembled delivery. The bolted sheet steel construction with solid fixed frame is designed for robust applications in controlled indoor areas.

• 12U in 19-inch version with 450 mm depth – Creates a clearly defined installation situation for network and IT components.
• Unassembled flat-pack design with bolted fixed frame – Facilitates transport and storage and supports rational self-assembly.
• Front door as a glass door with latch lock and viewing window made of certified safety glass – Enables visual inspection and flexible adjustment thanks to the replaceable door hinge.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and self-ventilated design. The IP20 protection class, the load capacity of 60 kg, the powder-coated surface and the cable entries over the roof, floor and rear support a clean integration of 19-inch components. The maximum distance between the 19" levels is 340 mm and the installation depth is 380 mm.

Technical details
• Number of doors: 1
• Degree of protection: IP20
• Type of ventilation: passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing Flat Pack 12U, Depth 450 mm, RAL7035

- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Reversible front door hinging: Yes
- Replaceable profile half-cylinder in front door: optional (compact swing handle item no. 699989)
- Scope of delivery: 1x cabinet, earthing cable, 2x keys
- Packaging: 1 carton
- Number of rack units (U): 12 U
- Width: 570 mm
- Height: 635 mm
- Depth: 450 mm
- Installation depth min. - max.: 380 mm
- Cable entry roof/floor: roof + floor + 2 x back, each 230 x 41 mm
- Max. distance of the 19" planes: 340 mm
- Payload: 60 kg
- Design: with fixed frame
- Material: Steel
- Finish of the surface: powder-coated
- Colour: grey

Technical properties	
Cabinet Series	19" Wall Housing FLAT PACK, un-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 230 x 41 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, unassembled
Installation depth min. - max.	380 mm
Material	Steel
Max. spacing of the 19" levels	340 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	1 carton
Scope of delivery	1x Cabinet, grounding cable, 2x keys

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing Flat Pack 12U, Depth 450 mm, RAL7035

Structure/Use	Steel sheet housing with very solid frame, self-ventilated, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691706FGR.1	19" Wall Housing Flat Pack 6U, Depth 450 mm, RAL7035	grey	450 mm	370 mm	60 kg	6 U	570 mm	7035
691709FGR.1	19" Wall Housing Flat Pack 9U, Depth 450 mm, RAL7035	grey	450 mm	500 mm	60 kg	9 U	570 mm	7035
691712FGR.1	19" Wall Housing Flat Pack 12U, Depth 450 mm, RAL7035	grey	450 mm	635 mm	60 kg	12 U	570 mm	7035
691715FGR.1	19" Wall Housing Flat Pack 15U, Depth 450 mm, RAL7035	grey	450 mm	770 mm	60 kg	15 U	570 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION