


DATASHEET

19" Wall Housing Flat Pack 15U, Depth 450 mm, RAL9005



General data

The 19" Flat Pack wall enclosure in black RAL 9005 with a depth of 450 mm is designed as a robust solution for demanding installations. The unassembled design facilitates transport and storage, while the bolted fixed frame enclosure provides a stable basis for 19-inch assembly.

- 15U 19-inch format with 450 mm depth – Creates a compact installation situation for 19-inch components and supports a well-defined structure in the control room.
- Unassembled flat-pack design with bolted frame – simplifies transport and storage and reduces the hassle of self-assembly.
- Glass door with latch lock and viewing window made of certified safety glass (4 mm) – Allows visual inspection of the contents and offers a flexible front design.

The technical design combines a sheet steel housing with a very solid frame and self-ventilated, passive air ducting. The powder-coated surface, the IP20 protection class and the load capacity of 60 kg are designed for use in controlled

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing Flat Pack 15U, Depth 450 mm, RAL9005

indoor areas. Cable entries over the roof, floor and rear support a clean integration of the components. The front is designed for a mounting level at the front and the replaceable door hinge increases adaptability to different installation situations.

Technical details

- Number of doors: 1
- Degree of protection: IP20
- Type of ventilation: passive
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Reversible front door hinging: Yes
- Replaceable profile half-cylinder in front door: optional (compact swing handle item no. 699989)
- Scope of delivery: 1x cabinet, earthing cable, 2x keys
- Packaging: 1 carton

Technical properties	
Cabinet Series	19" Wall Housing FLAT PACK, un-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 230 x 41 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, unassembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	1 carton
Scope of delivery	1x Cabinet, grounding cable, 2x keys
Structure/Use	Steel sheet housing with very solid frame, self-ventilated, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

19" Wall Housing Flat Pack 15U, Depth 450 mm, RAL9005

Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691706FTS.1	19" Wall Housing Flat Pack 6U, Depth 450 mm, RAL9005	black	450 mm	370 mm	60 kg	6 U	570 mm	9005
691709FTS.1	19" Wall Housing Flat Pack 9U, Depth 450 mm, RAL9005	black	450 mm	500 mm	60 kg	9 U	570 mm	9005
691712FTS.1	19" Wall Housing Flat Pack 12U, Depth 450 mm, RAL9005	black	450 mm	635 mm	60 kg	12 U	570 mm	9005
691715FTS.1	19" Wall Housing Flat Pack 15U, Depth 450 mm, RAL9005	black	450 mm	770 mm	60 kg	15 U	570 mm	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

