DATASHEET


19" Wall Housing Flat Pack 15U, Depth 600 mm, RAL9005













General data

The 19" 15U wall enclosure Flat Pack with a depth of 600 mm in RAL 9005 is designed as a robust solution for demanding applications. The unassembled flat pack design facilitates transport and storage. The bolted frame with fixed frame creates a stable basis for 19-inch installation.

• 15U in 19-inch design with 600 mm depth – Creates a well-defined installation situation for network and IT components in wall-mounted applications.
• Unassembled flat-pack design with bolted frame – Reduces the effort involved in transport and assembly and provides a solid base in operation.
• Front door as glass door with latch lock and viewing window made of certified safety glass – Enables visual inspection and combines transparency with practical access protection.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and self-ventilated design. The construction made of powder-coated sheet steel is designed for controlled indoor areas and

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

19" Wall Housing Flat Pack 15U, Depth 600 mm, RAL9005

achieves protection class IP20. Cable entries via roof, floor and two rear sides as well as the load capacity of 60 kg support a clean integration of the components. The scope of delivery includes a cabinet, earthing cable and two keys.

Technical details
- Number of doors: 1
- Degree of protection: IP20
- Type of ventilation: passive
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Replaceable profile half-cylinder in front door: optional (compact swing handle item no. 699989)
- Scope of delivery: 1x cabinet, earthing cable, 2x keys
- Packaging: 1 carton

Technical properties	
Cabinet Series	19" Wall Housing FLAT PACK, un-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 230 x 41 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, unassembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	1 carton
Scope of delivery	1x Cabinet, grounding cable, 2x keys
Structure/Use	Steel sheet housing with very solid frame, self-ventilated, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing Flat Pack 15U, Depth 600 mm, RAL9005

With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691709FTS.2	19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL9005	black	600 mm	500 mm	60 kg	9 U	570 mm	9005
691712FTS.2	19" Wall Housing Flat Pack 12U, Depth 600 mm, RAL9005	black	600 mm	635 mm	60 kg	12 U	570 mm	9005
691715FTS.2	19" Wall Housing Flat Pack 15U, Depth 600 mm, RAL9005	black	600 mm	770 mm	60 kg	15 U	570 mm	9005
691721FTS.2	19" Wall Housing Flat Pack 21U, Depth 600 mm, RAL9005	black	600 mm	1040 mm	60 kg	21 U	570 mm	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION